

## ***TimeMate SPCR65***

Elegant Smart Card Device with IP65 weatherproof structure.



Smart Card IP based access control unit providing high-level security for small-to-medium sized systems to larger enterprise-level systems. Featuring next generation IP access control system structure, it acts as a smart reader and controller with distributed intelligence concept. With its RS485 and Wiegand interfaces, it can also fit in your legacy systems. It is fully compatible with Intelliob TimeMate software systems, offering extra flexibility of biometric IP access control and Time Attendance Systems to meet different needs and requirements.



POE



IP65



TCP/IP



RF CARD



<p><b>Features:</b></p> <p><b>TCP/IP &amp; Network interfaces</b> IP enabled distributed access control system by ethernet (DHCP or static IP) and RS485 interfaces</p> <p><b>Power over Ethernet (POE)</b> communication and power over a simple CAT5 or 6 cable/supplies up to 600mA of 12Vdc to locking devices</p> <p><b>Enterprise-level access control capacity</b> controls up to 40,000 users, 128 time schedules, 128 access groups and 64 zones</p> <p><b>IP65 weatherproof structure</b> rugged structure for outdoor installation, operates between -20 ~ 50 Degrees Celsius.</p> <p><b>Easier installation &amp; operation</b> direct lock relay and Wiegand connection/ command card operation (add/delete users)</p> <p><b>Sleek &amp; aesthetic design</b> slim and sleek size for narrow door frames/ multi-color LED &amp; buzzer for indication</p> <p><b>Integrated with TimeMate Software</b> Time Attendance management solution available with Intelliob TimeMate software.</p>	<p><b>HW Specifications:</b></p> <p>CPU 400MHz DSP</p> <p>Memory 8MB Flash + 16MB SDRAM</p> <p>RF Card 13.56MHz Mifare (XPM)</p> <p>User Capacity 40,000 users</p> <p>Log Capacity 50,000 log records</p> <p>Communication Interfaces TCP/IP, RS485</p> <p>Wiegand Interface Input or output (switchable)</p> <p>I/O 2 x TTL inputs, 1 x relay, 1 x tamper</p> <p>User Interfaces Multi-color LED</p> <p>IP Rate: IP65 (Water Proof Device)</p> <p>Operating Temperature -20° ~ 50°</p> <p>Operating Voltage 12V DC</p> <p>Size (W x H x D) 45 x 130 x 27mm</p> <p>Certificates CE, FCC, KCC, ROHS</p>
--	--

*Integrated with TimeMate Software by*

**Intelliob Technologies Pvt Ltd.**  
C-110 Gambhir Estate,  
Off Aarey Road,  
Goregoan East,  
Mumbai,  
India.  
Phone: 022 28791193 / 022 28768198  
Web: [www.intelliob.com](http://www.intelliob.com)  
Web: [www.timemate.in](http://www.timemate.in)